



When image experience matters.

MX55HD-L-ERO

Specification	Detail
Planar Part Number	997-6410-00
Technology	Commercial-grade direct view LCD
Diagonal Size	55 inches
Aspect Ratio	N/A
Native Resolution Panels	1920 x 1080
Bezel Width	5.5 mm
Brightness (typ)	800 cd/m ² or nits
Response Time (typ)	8 ms
Contrast ratio (full field)	3500:1
Full viewing angle	178°
Backlight life (1/2 brightness)	50,000 Hrs
Mounted depth	3.8" wall to front of screen
Acoustic noise	Fanless operation
Heat load	620 BTU per hour at 500 nit
Operating temperature range	5 - 40 Degrees C
Operating humidity range	20-90% RH non-condensing
Backlight control	Individual and wall control
Backlight sensing and reporting	At display level
Display module position sensing	Auto-sensing integrated
Power Consumption (max)	182 watts (typical)
Power supply voltage	100-230V AC ± 10%, 50 to 60 Hz
Power status	Diagnostics LEDs, health monitoring and alerts
Safety regulations	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
Data Inputs	4 Single Link DVI Inputs, 1 Dual Link DVI Inputs
Control	IR Remote, RS232, Ethernet (optional)
Per Panel Dimensions (Including Mount)	47.87" x 27.04" x 3.8"
Per Panel Weight (Including Mount)	74 lbs
Wall Dimensions (WxHxD)	N/A

Wall Dimensions (WxHxD) including stand	N/A
Shipping weight	150 lbs
In the Box	N/A
UPC	810689064107

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 9/30/2013

(c)Copyright 2013 Planar Systems, Inc. All rights reserved